

BBP®12 Label Printer



BradyID.com/bbp12

Efficiency, versatility and performance – all packed into one multi-use label printer. With high speed printing, a small footprint and a simple, user-friendly design, the BBP®12 Label Printer packs a lot of punch into one compact tool.

From general identification to adhesive wire and asset tracking labels, the BBP12 label printer offers a variety of high performance materials.

Simple, Efficient Design

- Specifically designed small-core media rolls and ribbons provide fast installation and reduce change-over time
- Compatible with 3"-core media rolls if using the external media holder (sold separately)
- Easy set-up & calibration
- Compact size won't clutter your workplace or bench

Performance

- Sharp 300 dpi printing on labels up to 4" wide
- Fast print speed up to 4 inches per second
- Over 800 varieties of labels, including external-feed bulk rolls and custom parts
- Centering ribbon spindle virtually eliminates ribbon wrinkle

Complete the Brady BBP®12 Printing System with

■ Brady LabelMark[™] Labeling Software



Printer Specs

| Physical Properties | |
|-------------------------------|---|
| Enclosure | Clamshell mechanism design |
| Dimensions | 10.21" (L) x 7.99" (W) x 7.54" (H) 259.3 mm (L) x 203 mm (W) x 191.5 mm (H) |
| Weight | 5.07 lb (2.3 kg) |
| Printing Method | Thermal Transfer and Direct Thermal |
| Resolution | 300 DPI |
| Print Speed | 4 ips |
| Ribbon capacity | 360 ft (110 m), 0.5" core |
| Label roll capacity | 5" OD (8" with external media holder) |
| Electronics | |
| Processor | 32-bit RISC CPU |
| Memory | 128MB Flash memory, 64MB SDRAM, SD card slot, up to 32 GB |
| Power | External universal switching power supply |
| Operation switch, button, LED | One power switch, 6 operation buttons, 2.3" color LCD Display, One LED (3 colors: green, amber, red) |
| Sensors | Gap transmissive sensor, Black mark reflective sensor, Head open sensor, Ribbon end sensor |
| Interface | |
| Interface | USB 2.0 (high speed mode), RS-232C (Serial), Internal Ethernet, USB host |
| Bar Code | |
| 1D bar code | Code 39, Code 39 with check digit, Code 93, Code 128UCC, Code 128 subset A, B, C, Codabar, Interleave 2 of 5, Interleaved 2 of 5 with check digit, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, MSI, MSI with check digit, PLESSEY, POSTNET, Logmars, Code 11, Code 49, China post, ITF14, TELEPEN, TELEPENN, PLANET, Deutsche Post Indentcode, Duetsche Post Leitcode |
| 2D bar code | GS1 DataBar, GS1 DataMatrix, Maxicode, AZTEC, PDF417, QR Code, Micro PDF 417 |
| Fonts | |
| Internal fonts | 8 alpha-numeric bitmap fonts Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font |

Command Set/Printer Language

TSPL-EZ[™] (compatible to EPL, ZPL, ZPLII)

FCC, CE, EAC, RCM, C-UL US, TUV/Safety, CCC

Environment Compliant

RoHS, WEEE

| 13PL-EZ (Companible to EPL, ZPL, ZPLII) | | |
|---|---|--|
| Media | | |
| Media type | Continuous, die-cut, fan-fold, tag, notch, black mark | |
| Minimum label height | 0.39" (9.9 mm) | |
| Media width | 0.79" - 4.6" (20 - 118 mm) | |
| Max print width | 4.15" (105.6 mm) | |
| Media holder | 1" and 1.5" core (3" core with external media holder) | |
| Media thickness | 0.002" - 0.0075" (0.06 - 0.19 mm) | |
| Environment Condition | | |
| Operation | 41°F-104°F (5°-40°C), 25-85% non-condensing | |
| Storage | -40°F-140°F (-40°-60°C), 1 0-90% non-condensing | |
| Safety Regulation | | |



| Part Number | Description |
|-------------|---|
| BBP12-US | BBP12 Label Printer |
| BBP12-US-LM | BBP12 Label Printer with LabelMark [™] 6 Pro Software |
| BBP12-U | BBP12 External Media Holder (for 3" core rolls) |



Brady360® 5-Year Warranty

We have you Covered.

We always stand behind our products to make sure they exceed your expectations and to deliver you an unrivaled customer experience. We've strengthened our commitment to you with a **5-year printer warranty standard and free of charge** on our benchtop printer models.*

Our 5-year warranty covers repair parts & labor, one print head replacement, a free loaner printer, a stress-free printer setup session, and much more. You also have access to additional fee-based support, including an on-site repair service, custom programming and advanced integrations services.

*Excludes repairs due to negligence, Wraptor™ model and handheld models. See www.BradylD.com/brady360 for full details & restrictions.

For more information, contact your Brady representative or visit BradyID.com/bbp12.

USA

Customer Service: 1-888-272-3946 Inside Sales: 1-888-311-0775 www.BradyID.com

Canada

Customer Service: 1-800-263-6179 www.BradyCanada.ca

Mexico

1-800-262-7777

Inside Sales: 1-800-262-7777 ext 177 www.BradyLatinAmerica.com

