

COLLAPSIBLE GATE VALVE LOCKOUTS

SAFELY LOCK OUT GATE VALVES FROM 76 UP TO 457 MM WITH THE COLLAPSIBLE GATE VALVE LOCKOUT.

Brady's collapsible gate valve design provides secure lockout for a wider range of valves, with the use of fewer devices. These covers easily rotate around valve handles to the fully engaged position, while also folding into smaller sizes for easy storage on maintenance carts and in lockout kits.

- Rugged, injection moulded styrene construction that can withstand harsh outdoor conditions
- Up to two padlocks can be attached directly on the Collapsible Gate Valve Lockout, and even more padlocks can be added to safeguard larger maintenance teams by using Brady's Lockout/Tagout safety hasp
- Easy to apply: rotates around valves and fully covers them to make them inoperable
- Easy to store and carry: folds to 1/3 of its full size
- Flexible: 3 size variations can lock valves ranging from 76 mm up to 457 mm
- Withstands temperatures from -40 °C to +100 °C
- Unique knockout centre accommodates OS & Y or "rising stem" valves

Comes with danger labels in English, Spanish and French

Order Reference	Hand Wheel Diameter (mm)	Height (mm)	Depth (mm)	Diameter (mm)	Max. Shackle Diameter (mm)	Min. Shackle Clearance (mm)	Quantity
148646	330 - 457	472.70	101.10	500.40	9.53	12.70	1
148647	178 - 330	346.20	101.10	374.00	9.53	12.70	1
148648	76 - 178	189.00	78.70	229.40	9.53	12.70	1



i Consult the technical datasheet LOTO-81 on www.bradyeurope.com/tds



Brady Collapsible Gate Valve Lockouts for 330 - 457 mm diam.



Brady Collapsible Gate Valve Lockouts for 178 - 330 mm diam.



Brady Collapsible Gate Valve Lockouts for 76 - 178 mm diam.

