



GENERAL PRODUCT SPECIFICATION

Item No.	CHBB15
-----------------	--------

Date	8-10-14	Replaces		No. Pages	1
-------------	---------	-----------------	--	------------------	---

Product Description:

Style	Blanket Roll
Item Size (each)	15"wide x 100'long
Color	Yellow on Natural White
Composition	> 99% Polypropylene
Structure	The bottom layer is a white, spunbond nonwoven, treated with a 1-mil thick anti-skid film. The middle layer is a yellow meltblown nonwoven sorbent comprised of micro-fiber mechanically entangled. Top layer having a yellow lint & abrasion resistant printed spunbond cover-stock (non-woven, continuous filaments randomly oriented and thermally point bonded [15-30 micron diameters]). The (3) plies are secured together with bonded dimpling.
Technology	Meltblown, Spunbond, Bonding
Absorbency	Universal (Hydrophilic + Oleophilic)
Bonding	Mechanical Entanglement; Bonded (staggered pattern)

Intended Application	Durable high strength barrier sorbent track mat blanket, particularly suitable at railway sites.
-----------------------------	--

Absorbency Capacity	13.4 gal. per roll (saturated; medium viscosity-9x)
----------------------------	---

Packaging Description:

Package configuration	Roll	Pkg. Weight	11 lbs
Items per Package	1 Blanket	Pkg. Dimensions	17" x 17" x 16" H
Container type	Carton		

Physical Properties:

<u>Parameter</u>	<u>SPC Test Method</u>	<u>Units</u>	<u>Nominal</u>	<u>(+/-)Tolerance</u>
Basis Weight	SPCTM-002	G/M2	340	39
Caliper	SPCTM-003	mils	140	30
Absorbency** (med.visc.)	SPCTM-004B	gL/gS	11.7	2
Tensile - 3"	SPCTM-007	lbs	26.2	4
Color & Hand Feel	Visual	-----	Yellow & White	per standard
Bond Pattern	Visual	-----	per standard	per standard
Net Roll Weight	W.I.P.	lbs	9	3

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.

**** The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.**

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.
Labeling	Each package to be clearly labeled with Company Name, Address, Item No., Date, and/or Package Code (Bar Code).
Certification	Make no changes in basic process or composition without notifying customer. Claims for non-conformance of goods must be made within 60-days of delivery.