



GENERAL PRODUCT SPECIFICATION

PLEASE REFER TO UN100-E AND HAZ412 FOR INDIVIDUAL SPECS

Item No.	SKH-ATK
-----------------	----------------

Date	16-6-2017	Replaces	4-11-11	No. Pages	1
-------------	-----------	-----------------	---------	------------------	---

Product Description:

Style	Spill Kit - "Attack Pac"
Item Size (each)	Bag
Packaging	Silver Vacuum-Sealed bag. A single metal grommet is pressed into the top center of the bag, above the seal but at least 7/8" away from the top edge of the bag.
Contents (each)	15 UN100-E (41 cm x 51 cm) Pads, 3 HAZ412 (7.6 cm x 122 cm) Soc's, 1 pair of goggles, 1 pair of Nitrile gloves, 1x 6-mil disposal bag and 1 instruction sheet.
Color	Silver
Absorbency	Hydrophilic + Oleophilic + Hazardous Chemicals

Intended Application	Emergency kits for fast response of spills
-----------------------------	--

Absorbency Capacity	91 l per case (saturated; medium viscosity)
----------------------------	---

Packaging Description:

Package configuration	Case	Pkg. Weight	10kg (8.5kg)
Items per Package	4 Packs/Case	Pkg. Dimensions	50 cm x 54 cm x 52cm (H)
Container type	Carton		

Physical Properties:

<u>Parameter</u>	<u>SPC Test Method</u>	<u>Units</u>	<u>Nominal</u>	<u>(+/-)Tolerance</u>
Color	Visual	-----	Silver	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.
Labeling	Each package to be clearly labeled with Company Name, Address, Item No., Date, and/or Package Code (Bar Code).
Certification	Make no changes in basic process or composition without notifying customer. Claims for non-conformance of goods must be made within 60-days of delivery.

Note: All values shown are averages and should not be used for specification purposes. Test data and test results contained in this document are for general information only and shall not be relied upon by Brady customers for designs and specifications, or be relied on as meeting specified performance criteria. Customers desiring to develop specifications or performance criteria for specific product applications should contact Brady for further information. Product

compliance information is based upon information provided by suppliers of the raw materials used by Brady to manufacture this product or based on results of testing using recognized analytical methods performed by a third party, independent laboratory. As such, Brady makes no independent representations or warranties, express or implied, and assumes no liability in connection with the use of this information.

WARRANTY Brady products are sold with the understanding that the buyers will test them in actual use and determine for themselves their adaptability to their intended uses. Brady warrants to the buyers that its products are free from defects in material and workmanship, but limits its obligation under this warranty to replacement of the product shown to Brady's satisfaction to have been defective at the time Brady sold it. This warranty does not extend to any persons obtaining the product from the buyers. This warranty is in lieu of any other warranty, express or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose, and of any other obligations or liability on Brady's part. Under no circumstances will Brady be liable for any loss, damage, expense, or consequential damages of any kind arising in connection with the use, or inability to use,

WH Brady NV – Division SPC International, Atealaan 71, I.Z. Klein Gent, B-2200 Herentals, Belgium
Tel +32(0)14 321855 Fax +32(0)14 320440 www.bradyeurope.com