



POWERFUL PRODUCTIVITY FOR THE JOBSITE

Brady M210 and M211 Portable Label Printers

Durable. Intuitive. **Ready for any jobsite.**

**Identify wires, cables, racks, bins and more
with durable labels up to 0.75" wide.**



M210 Label Printer

Take on your toughest on-site labeling challenges to get the job done right. With smart automatic formatting, all you need to do is drop in a label cartridge, type and print.



M211 Label Printer

Optimized for mobile so you can seamlessly design, view and print labels with the Express Labels Mobile app. Design on screen. Print on demand. Label right on-site.





MEET THE DEMANDS OF ON-SITE LABELING

THE M210

Rugged, reliable and ready for the toolbox
so you can quickly and easily print labels anywhere



The tough, intuitive labeler that belongs on any jobsite

Do more with these time-saving features:

- ▶ Create and print with a built-in keypad
- ▶ 11 pre-loaded application design guides
- ▶ Ability to create UPC, DataMatrix and QR codes
- ▶ Store up to 12 label files up to 2MB
- ▶ Prints up to 2,000 on a single charge with a Li-Ion battery pack*
- ▶ Onboard label material gauge

* Sold separately. Included in all M210 Printer Kits.

PRINT THE WAY YOU WORK



CUSTOM
DESIGN GUIDES



CHOOSE FROM 90+
EASY-TO-LOAD
CARTRIDGES




BUILT TO
WITHSTAND
TOUGH JOBSITE



DESIGN. PREVIEW. PRINT. ALL FROM YOUR PHONE.

THE M211

Bluetooth enabled so you can get the job done
right from our industry-leading Express Labels Mobile app



Label creation is just a tap away
for on-the-go printing

Do more with these time-saving features:

- ▶ 20+ barcode/QR code types, 85 fonts and over 1,400 symbols
- ▶ Resists 6-foot drops, 250-lb. crushes and military-grade shocks
- ▶ 90+ cartridges and 12 material types
- ▶ Keep work moving with label design guides
- ▶ Prints up to 300 labels on a full charge with an internal Li-Ion battery
- ▶ Auto label cutter

PRINTING OPTIMIZED FOR MOBILE



DESIGN
ON SCREEN



PRINT ON
DEMAND



LABEL
ON-SITE

KITS AND ACCESSORIES TO STREAMLINE WORKFLOWS

Unlock the full potential of your label printer with our range of convenient kits and accessories. All-in-one kits contain a range of accessories, from hands-free facilitators to organized storage and transportation solutions, designed to streamline your labeling workflow.

PRINTERS

M211 LABEL PRINTER



What's included?

M211 Printer, M21-750-499 Label Cartridge and AC Adapter

M210 LABEL PRINTER



What's included?

M210 Label Printer and M21-750-499 Label Cartridge

ACCESSORIES

Magnet

For hands-free operation

The Magnet accessory offers a convenient option to attach your printer to panels, I-beams and any other magnetic-receptive surface.

Power Brick

For power on the go

Use the high-capacity Power Brick for your printer, phone or tablet to keep everything running smoothly.

M210 & M211




M21-MAGNET

M210



M210-PWR-KIT

M211



M211-M511-POWER

KITS

M211 PORTABLE BLUETOOTH LABEL PRINTER KIT

What's included?

M211 Printer, M21-750-499 Label Cartridge, AC Adapter, Belt Clip, Power Brick, Hard Case and Magnet



M211-KIT

M210 HANDHELD LABEL MAKER KIT

What's included?

M210 Label Printer, AC Adapter/Battery Charger, M21-750-499 Label Cartridge, Li-Ion Rechargeable Battery, Replacement Power Cord and Hard Case



M210-KIT

Hard Case & Soft Case

For printer protection and storage

Protect your printer and keep accessories and label cartridges on hand and organized.

Belt Clip & Utility Hook

For hands-free transport

Easily attach your printer to your tool belt, cart, rack or bucket organizer with the Belt Clip or Utility Hook.

Rechargeable Battery Pack

For longer battery life

Work longer and with cordless printer operation with the Rechargeable Battery Pack.

AC Adapter

For power when you need it

Power your printer without the need for recharging or replacing batteries.

M210 & M211



M210-HC



BMP-SC-1

M210 & M211



M21-BELTCLIP

M210



M210-TOOL

M210



M210-BATTERY

M210



M210-AC

M211



M211-M511-AC

M211 SOFTWARE TO MAKE LABEL CREATION EASY

Software options for the M211 boost productivity by reducing manual input, automating tasks and simplifying processes.



Express Labels Mobile App

Label creation, just a tap away

- ▶ Preview labels before printing, ensuring no labels are wasted
- ▶ Visual design guides simplify advance label creation for wraps, flags, breaker boxes, patch panels, safety labels and more
- ▶ Save and share labels to eliminate time creating new labels from scratch



Software Development Kit (SDK)

One simple integration to print from your software

- ▶ Employees can use their own Android or iOS web-based software apps to print labels for a seamless way to get data to a Brady printer
- ▶ The SDK Library connects, retrieves, monitors and supports data for faster and more efficient workflows
- ▶ A versatile technology that can be used with select Brady Bluetooth-enabled printers



SAY HI TO BRADYVOICE™ LABELING ASSISTANT



- ▶ Available on Express Labels Mobile, BradyVoice offers a faster, more efficient way to label. Packed with time-saving features like quick formatting, intuitive voice recognition and automatic sizing, BradyVoice harnesses the power of your voice to streamline labeling tasks and maximize productivity.



All-Weather

Get extra durability outdoors and in tough, industrial workspaces. Choose labels that are reflective or resistant to UV light, chemicals, salt spray and cleaners.




Fig. 29




Fig. 33



All-Weather Vinyl Labels

Make labels that withstand up to 10 years of outdoor abuse with this low-shrink vinyl label material (B-595). Temp. range: -40°F to 180°F (-40°C to 82°C). UL recognized.

Catalog #	B#	Material	Color	Finish	Label Width A inch (mm)	Label Height B inch (mm)	Labels per Cartridge	Figure
M21-11-595-WT	B-595	Vinyl	Black on White	Gloss	0.750 (19.1)	0.500 (12.7)	140	Fig 29
M21-18-595-WT	B-595	Vinyl	Black on White	Gloss	1.000 (25.4)	0.750 (19.1)	121	Fig 29
M21-131-595-WT	B-595	Vinyl	Black on White	Gloss	1.000 (25.4)	0.500 (12.7)	121	Fig 29
M21-136-595-WT	B-595	Vinyl	Black on White	Gloss	1.500 (38.1)	0.750 (19.1)	91	Fig 29
M21-137-595-WT	B-595	Vinyl	Black on White	Gloss	2.000 (50.8)	0.750 (19.1)	73	Fig 29
M21-250-595-WT	B-595	Vinyl	Black on White	Gloss	0.250 (6.4)	-	21 ft (6.4 m), cont.	Fig 33
M21-250-595-YL	B-595	Vinyl	Black on Yellow	Gloss	0.250 (6.4)	-	21 ft (6.4 m), cont.	Fig 33
M21-375-595-BK	B-595	Vinyl	White on Black	Gloss	0.375 (9.5)	-	21 ft (6.4 m), cont.	Fig 33
M21-375-595-BL	B-595	Vinyl	White on Blue	Gloss	0.375 (9.5)	-	21 ft (6.4 m), cont.	Fig 33
M21-375-595-BR	B-595	Vinyl	White on Brown	Gloss	0.375 (9.5)	-	21 ft (6.4 m), cont.	Fig 33
M21-375-595-GN	B-595	Vinyl	White on Green	Gloss	0.375 (9.5)	-	21 ft (6.4 m), cont.	Fig 33
M21-375-595-GY	B-595	Vinyl	Black on Gray	Gloss	0.375 (9.5)	-	21 ft (6.4 m), cont.	Fig 33
M21-375-595-OR	B-595	Vinyl	Black on Orange	Gloss	0.375 (9.5)	-	21 ft (6.4 m), cont.	Fig 33
M21-375-595-PL	B-595	Vinyl	White on Purple	Gloss	0.375 (9.5)	-	21 ft (6.4 m), cont.	Fig 33
M21-375-595-RD	B-595	Vinyl	White on Red	Gloss	0.375 (9.5)	-	21 ft (6.4 m), cont.	Fig 33
M21-375-595-WT	B-595	Vinyl	Black on White	Gloss	0.375 (9.5)	-	21 ft (6.4 m), cont.	Fig 33
M21-375-595-YL	B-595	Vinyl	Black on Yellow	Gloss	0.375 (9.5)	-	21 ft (6.4 m), cont.	Fig 33
M21-500-595-BK	B-595	Vinyl	White on Black	Gloss	0.500 (12.7)	-	21 ft (6.4 m), cont.	Fig 33
M21-500-595-BL	B-595	Vinyl	White on Blue	Gloss	0.500 (12.7)	-	21 ft (6.4 m), cont.	Fig 33
M21-500-595-BR	B-595	Vinyl	White on Brown	Gloss	0.500 (12.7)	-	21 ft (6.4 m), cont.	Fig 33
M21-500-595-GN	B-595	Vinyl	White on Green	Gloss	0.500 (12.7)	-	21 ft (6.4 m), cont.	Fig 33
M21-500-595-GY	B-595	Vinyl	Black on Gray	Gloss	0.500 (12.7)	-	21 ft (6.4 m), cont.	Fig 33
M21-500-595-OR	B-595	Vinyl	Black on Orange	Gloss	0.500 (12.7)	-	21 ft (6.4 m), cont.	Fig 33
M21-500-595-PL	B-595	Vinyl	White on Purple	Gloss	0.500 (12.7)	-	21 ft (6.4 m), cont.	Fig 33
M21-500-595-RD	B-595	Vinyl	White on Red	Gloss	0.500 (12.7)	-	21 ft (6.4 m), cont.	Fig 33
M21-500-595-WT	B-595	Vinyl	Black on White	Gloss	0.500 (12.7)	-	21 ft (6.4 m), cont.	Fig 33
M21-500-595-YL	B-595	Vinyl	Black on Yellow	Gloss	0.500 (12.7)	-	21 ft (6.4 m), cont.	Fig 33
M21-750-595-BK	B-595	Vinyl	White on Black	Gloss	0.750 (19.1)	-	21 ft (6.4 m), cont.	Fig 33
M21-750-595-BL	B-595	Vinyl	White on Blue	Gloss	0.750 (19.1)	-	21 ft (6.4 m), cont.	Fig 33
M21-750-595-BR	B-595	Vinyl	White on Brown	Gloss	0.750 (19.1)	-	21 ft (6.4 m), cont.	Fig 33
M21-750-595-GN	B-595	Vinyl	White on Green	Gloss	0.750 (19.1)	-	21 ft (6.4 m), cont.	Fig 33
M21-750-595-GY	B-595	Vinyl	Black on Gray	Gloss	0.750 (19.1)	-	21 ft (6.4 m), cont.	Fig 33
M21-750-595-OR	B-595	Vinyl	Black on Orange	Gloss	0.750 (19.1)	-	21 ft (6.4 m), cont.	Fig 33
M21-750-595-PL	B-595	Vinyl	White on Purple	Gloss	0.750 (19.1)	-	21 ft (6.4 m), cont.	Fig 33
M21-750-595-RD	B-595	Vinyl	White on Red	Gloss	0.750 (19.1)	-	21 ft (6.4 m), cont.	Fig 33
M21-750-595-WT	B-595	Vinyl	Black on White	Gloss	0.750 (19.1)	-	21 ft (6.4 m), cont.	Fig 33
M21-750-595-YL	B-595	Vinyl	Black on Yellow	Gloss	0.750 (19.1)	-	21 ft (6.4 m), cont.	Fig 33



Heat Shrink

Choose industrial grade, heat-shrinkable sleeve labels for long-lasting wire and cable identification. Built to Naval Air Systems Command (NAVAIR) and industry-specific standards.




Fig. 58



PermaSleeve® Heat-Shrink Tubing

Permanently mark wires with the durable PermaSleeve® PS heat-shrink polyolefin sleeve label material (B-342). Temp. range: -67°F to 275°F (-55°C to 130°C). RoHS compliant and UL recognized.

Catalog #	B#	Material	Color	Finish	Approx Wire Gauge	Diameter as Supplied B inch (mm)	Recovered Diameter inch (mm)	Label Width A	Labels per Cartridge	Figure
M21-125-C-342	B-342	Polyolefin	Black on White	Matte	22 AWG - 16 AWG	0.125 (3.2)	0.047 (1.2)	0.235 (6.0)	7 ft (2.13 m), cont.	Fig 58
M21-125-C-342-YL	B-342	Polyolefin	Black on Yellow	Matte	22 AWG - 16 AWG	0.125 (3.2)	0.047 (1.2)	0.235 (6.0)	7 ft (2.13 m), cont.	Fig 58
M21-187-C-342	B-342	Polyolefin	Black on White	Matte	20 AWG - 10 AWG	0.187 (4.8)	0.062 (1.6)	0.335 (8.5)	7 ft (2.13 m), cont.	Fig 58
M21-187-C-342-YL	B-342	Polyolefin	Black on Yellow	Matte	20 AWG - 10 AWG	0.187 (4.8)	0.062 (1.6)	0.335 (8.5)	7 ft (2.13 m), cont.	Fig 58
M21-250-C-342	B-342	Polyolefin	Black on White	Matte	16 AWG - 8 AWG	0.250 (6.4)	0.093 (2.4)	0.439 (11.2)	7 ft (2.13 m), cont.	Fig 58
M21-250-C-342-YL	B-342	Polyolefin	Black on Yellow	Matte	16 AWG - 8 AWG	0.250 (6.4)	0.093 (2.4)	0.439 (11.2)	7 ft (2.13 m), cont.	Fig 58
M21-375-C-342	B-342	Polyolefin	Black on White	Matte	12 AWG - 4 AWG	0.375 (9.5)	0.125 (3.2)	0.645 (16.4)	7 ft (2.13 m), cont.	Fig 58
M21-375-C-342-YL	B-342	Polyolefin	Black on Yellow	Matte	12 AWG - 4 AWG	0.375 (9.5)	0.125 (3.2)	0.645 (16.4)	7 ft (2.13 m), cont.	Fig 58



Laboratory

Ensure lab samples remain legible, scannable and trackable in every extreme process: cryogenic, staining, solvents and processing fluids.



Fig. 33



Self-Laminating Cryogenic Polyester Labels

Securely label lab tubes and vials for cryogenic storage with this self-laminating, ultra-thin polyester label material (B-461).

Catalog #	B#	Material	Color	Finish	Label Width A inch (mm)	Roll Length B inch (mm)	Labels per Cartridge	Figure
M21-375-461	B-461	Polyester	Black on White	Matte	0.375 (9.5)	-	21 ft (6.4 m), cont.	Fig 33
M21-500-461	B-461	Polyester	Black on White	Matte	0.500 (12.7)	-	21 ft (6.4 m), cont.	Fig 33
M21-750-461	B-461	Polyester	Black on White	Matte	0.750 (19.1)	-	21 ft (6.4 m), cont.	Fig 33



Solvent Resistant Polyester Labels

Easily label lab slides and well plates with the B-488 high-performance polyester label material.

Catalog #	B#	Material	Color	Finish	Label Width A inch (mm)	Roll Length B inch (mm)	Labels per Cartridge	Figure
M21-375-488	B-488	Polyester	Black on White	Matte	0.375 (9.5)	-	21 ft (6.4 m), cont.	Fig 33
M21-500-488	B-488	Polyester	Black on White	Matte	0.500 (12.7)	-	21 ft (6.4 m), cont.	Fig 33
M21-750-488	B-488	Polyester	Black on White	Matte	0.750 (19.1)	-	21 ft (6.4 m), cont.	Fig 33



Chemical and Temperature Resistant Polypropylene Labels

Mark dry, room temperature specimen containers with this economical matte white polypropylene label material (B-7425). Temp. range: -320°F to 248°F (-195°C to 120°C).

Catalog #	B#	Material	Color	Finish	Label Width A inch (mm)	Roll Length B inch (mm)	Labels per Cartridge	Figure
M21-375-7425	B-7425	Polypropylene	Black on White	Matte	0.375 (9.5)	-	21 ft (6.4 m), cont.	Fig 33
M21-500-7425	B-7425	Polypropylene	Black on White	Matte	0.500 (12.7)	-	21 ft (6.4 m), cont.	Fig 33
M21-750-7425	B-7425	Polypropylene	Black on White	Matte	0.750 (19.1)	-	21 ft (6.4 m), cont.	Fig 33



Water Dissolvable Paper Labels

Use this water dissolvable label material (B-403) for applications that require easily removable adhesive labels.

Catalog #	B#	Material	Color	Finish	Label Width A inch (mm)	Roll Length B inch (mm)	Labels per Cartridge	Figure
M21-500-403	B-403	Paper	Black on White	Matte	0.500 (12.7)	-	21 ft (6.4 m), cont.	Fig 33
M21-750-403	B-403	Paper	Black on White	Matte	0.750 (19.1)	-	25 ft (7.6 m), cont.	Fig 33



Multi-Purpose

Rely on white or clear labels for just about any industrial application that involves high or low temperatures, harsh environments or regulatory specifications. Choose from various adhesion types: standard, aggressive adhesive, ultra-aggressive adhesive or repositionable.




Fig. 29




Fig. 33



Harsh Environment Multi-Purpose Polyester Labels

UL recognized for outdoor use on glass, thermoset polyester plastic and polyvinyl fluoride plastic.

Catalog #	B#	Material	Color	Finish	Label Width A inch (mm)	Roll Length B inch (mm)	Labels per Cartridge	Figure
M21-7-423	B-423	Polyester	Black on White	Gloss	0.750 (19.1)	0.500 (12.7)	140	Fig 29
M21-17-423	B-423	Polyester	Black on White	Gloss	1.000 (25.4)	0.500 (12.7)	121	Fig 29
M21-18-423	B-423	Polyester	Black on White	Gloss	1.000 (25.4)	0.750 (19.1)	121	Fig 29
M21-30-423	B-423	Polyester	Black on White	Gloss	1.500 (38.1)	0.750 (19.1)	91	Fig 29
M21-137-423	B-423	Polyester	Black on White	Gloss	2.000 (50.8)	0.750 (19.1)	73	Fig 29
M21-250-423	B-423	Polyester	Black on White	Gloss	0.250 (6.4)	-	21 ft (6.4 m), cont.	Fig 33
M21-375-423	B-423	Polyester	Black on White	Gloss	0.375 (9.5)	-	21 ft (6.4 m), cont.	Fig 33
M21-500-423	B-423	Polyester	Black on White	Gloss	0.500 (12.7)	-	21 ft (6.4 m), cont.	Fig 33
M21-750-423	B-423	Polyester	Black on White	Gloss	0.750 (19.1)	-	21 ft (6.4 m), cont.	Fig 33



Harsh Environment Multi-Purpose Clear Polyester Labels

A permanent acrylic-based adhesive that withstands numerous solvents and can be applied to variable surfaces. Service temp: -94° to 212°F (-70° to 100°C). UL, CSA recognized.

Catalog #	B#	Material	Color	Finish	Label Width A inch (mm)	Roll Length B inch (mm)	Labels per Cartridge	Figure
M21-250-430	B-430	Polyester	Black on Clear	Gloss	0.250 (6.35)	-	21 ft (6.4 m), cont.	Fig 33
M21-375-430	B-430	Polyester	Black on Clear	Gloss	0.375 (9.53)	-	21 ft (6.4 m), cont.	Fig 33
M21-500-430	B-430	Polyester	Black on Clear	Gloss	0.500 (12.7)	-	21 ft (6.4 m), cont.	Fig 33
M21-750-430	B-430	Polyester	Black on Clear	Gloss	0.750 (19.05)	-	21 ft (6.4 m), cont.	Fig 33
M21-250-430-WT-CL	B-430	Polyester	White on Clear	Gloss	0.250 (6.35)	-	21 ft (6.4 m), cont.	Fig 33
M21-375-430-WT-CL	B-430	Polyester	White on Clear	Gloss	0.375 (9.53)	-	21 ft (6.4 m), cont.	Fig 33
M21-500-430-WT-CL	B-430	Polyester	White on Clear	Gloss	0.500 (12.7)	-	21 ft (6.4 m), cont.	Fig 33
M21-750-430-WT-CL	B-430	Polyester	White on Clear	Gloss	0.750 (19.05)	-	21 ft (6.4 m), cont.	Fig 33



Aggressive Adhesive Multi-Purpose Nylon Labels

Looking for a tough and versatile general-purpose label material? Look no further than the B-499 nylon cloth label material.

Catalog #	B#	Material	Color	Finish	Label Width A inch (mm)	Roll Length B inch (mm)	Labels per Cartridge	Figure
M21-11-499	B-499	Nylon	Black on White	Matte	0.750 (19.1)	0.500 (12.7)	140	Fig 29
M21-18-499	B-499	Nylon	Black on White	Matte	1.000 (25.4)	0.750 (19.1)	121	Fig 29
M21-131-499	B-499	Nylon	Black on White	Matte	1.000 (25.4)	0.500 (12.7)	121	Fig 29
M21-136-499	B-499	Nylon	Black on White	Matte	1.500 (38.1)	0.750 (19.1)	91	Fig 29
M21-137-499	B-499	Nylon	Black on White	Matte	2.000 (50.8)	0.750 (19.1)	73	Fig 29
M21-375-499	B-499	Nylon	Black on White	Matte	0.375 (9.5)	-	16 ft (4.8 m), cont.	Fig 33
M21-500-499	B-499	Nylon	Black on White	Matte	0.500 (12.7)	-	16 ft (4.8 m), cont.	Fig 33
M21-750-499	B-499	Nylon	Black on White	Matte	0.750 (19.1)	-	16 ft (4.8 m), cont.	Fig 33



Aggressive Adhesive Multi-Purpose Nylon Labels for Terminal Blocks

Aggressive Adhesive Multi-Purpose Nylon Labels are made of the same nylon cloth material designed for wire and cable wraps. These labels are narrow enough to align on terminal blocks and print with user-specified spacing when the printer is in terminal block mode.

Catalog #	B#	Material	Color	Finish	Label Width A inch (mm)	Roll Length B inch (mm)	Labels per Cartridge	Figure
M21-375-499-TB	B-499	Nylon	Black on White	Matte	0.375 (9.5)	-	16 ft (4.8 m), cont.	Fig 33
M21-500-499-TB	B-499	Nylon	Black on White	Matte	0.500 (12.7)	-	16 ft (4.8 m), cont.	Fig 33



Repositionable Multi-Purpose Vinyl Labels

Indoor/outdoor vinyl is a high-gloss, durable, flexible material designed with special adhesive to easily remove and reapply.

Catalog #	B#	Material	Color	Finish	Label Width A inch (mm)	Roll Length B inch (mm)	Labels per Cartridge	Figure
M21-500-581-WT	B-581	Vinyl	Black on White	Gloss	0.500 (12.7)	-	21 ft (6.4 m), cont.	Fig 33
M21-750-581-WT	B-581	Vinyl	Black on White	Gloss	0.750 (19.1)	-	21 ft (6.4 m), cont.	Fig 33



Adjustable

Get a grip on your wire and cable identification – Brady and VELCRO® Brand have partnered to bring you BradyGrip® Print-on Hook Material, an exclusive print-and-place material that can be easily applied, repositioned or removed.




Fig. 33



BradyGrip® Print-on-Hook Labels featuring VELCRO Brand Hook

Easily place, remove and reposition labels on cable bundles with the BradyGrip® Print-on Hook label material (B-414), paired with VELCRO® Brand ONE-WRAP® Rolls.

Catalog #	B#	Material	Color	Finish	Label Width A inch (mm)	Roll Length B inch (mm)	Labels per Cartridge	Figure
M21-250-414	B-414	Polyester	Black on White	Matte	0.250 (6.4)	-	10 ft (3.0 m), cont.	Fig 33
M21-500-414	B-414	Polyester	Black on White	Matte	0.500 (12.7)	-	10 ft (3.0 m), cont.	Fig 33
M21-750-414	B-414	Polyester	Black on White	Matte	0.750 (19.1)	-	10 ft (3.0 m), cont.	Fig 33



Wrap Around

Protect important wire and cable ID using labels with a clear laminating barrier. The clear vinyl resists abrasions and chemicals while keeping the white printable area intact.




Fig. 42




Fig. 42a



Self-Laminating Vinyl Wrap Around Labels

Mark cables and wires with the B-427 self-laminating vinyl label material, designed with a clear self-laminating protective layer. Temp. range: -40°F to 158°F (-40°C to 70°C). UL recognized.

Catalog #	B#	Material	Color	Finish	Approx Wire Gauge	Label Width A inch (mm)	Label Height B inch (mm)	Print-on Area C inch (mm)	Labels per Cartridge	Figure
M21-11-427	B-427	Vinyl	Black on White, Clear	Matte	22 AWG - 16 AWG	0.500 (12.7)	0.750 (19.1)	0.375 (9.5)	150	Fig 42
M21-18-427	B-427	Vinyl	Black on White, Clear	Matte	22 AWG - 16 AWG	1.000 (25.4)	0.750 (19.1)	0.375 (9.5)	121	Fig 42
M21-750-427	B-427	Vinyl	Black on White, Clear	Matte	20 AWG - 12 AWG	0.750 (19.1)	-	0.375 (9.5)	14 ft (4.3 m), cont.	Fig 42a
M21-1000-427	B-427	Vinyl	Black on White, Clear	Matte	16 AWG - 8 AWG	1.000 (25.4)	-	0.375 (9.5)	14 ft (4.3 m), cont.	Fig 42a
M21-1250-427	B-427	Vinyl	Black on White, Clear	Matte	12 AWG - 6 AWG	1.250 (31.8)	-	0.500 (12.7)	14 ft (4.3 m), cont.	Fig 42a
M21-1500-427	B-427	Vinyl	Black on White, Clear	Matte	10 AWG - 4 AWG	1.500 (38.1)	-	0.500 (12.7)	14 ft (4.3 m), cont.	Fig 42a



We make products that make the world a safer and smarter place. From the depths of the ocean to outer space, from the factory floor to the delivery room — **we're just about everywhere you look.**

► For more information or to learn more about our innovative products, visit BradyID.com or call 1-888-272-3946.

USA | BradyID.com
Customer Service: 1-888-272-3946

Canada | BradyCanada.ca
Customer Service: 1-800-263-6179

Mexico | BradyID.com.mx
Customer Service: 1-800-262-7777
Inside Sales: 1-800-262-7777 ext 177

